

# WeatherMaster™ Sealant

Titebond® WeatherMaster™ Sealant has been specifically formulated to outperform all other sealant technologies, including silicones, tripolymers and urethanes. This superior polymer formula provides the best possible performance on siding, windows, doors and vents. In addition to offering permanent flexibility, it provides unbeatable adhesion to wood, fiberboard, vinyl, aluminum, metal roofing, brass and other common building materials.

WeatherMaster™ Sealant is available in over 170 colors, all of which match today's popular siding colors, regardless of the material or manufacturer. If touch-ups are necessary, it is paintable in one hour after application. It is waterproof, extrudes in extreme weather conditions and is UV-resistant, making it the ideal choice for exterior applications. Safety is not compromised, as this sealant contains no solvents or isocyanates and is VOC-compliant.

## WeatherMaster™ Sealant Ordering Information

Cat. No.	Color	Size	Unit/Case	Ctn. lbs.	Cases/Pallet
44001	White	10.3 oz.	12	15	108
43991	Crystal Clear	10.3 oz.	12	10	108
44011	Translucent	10.3 oz.	12	10	108

More than 170 colors- please reference the WeatherMaster Color Reference Guide

Exceeds the requirements of ASTM C920 Type S, Grade NS, Class 25 and TTS-00230C.

## WeatherMaster™ Sealant Comparison Guide

	WeatherMaster	VOC Solvent	Silicone	Urethane	Tripolymer
Paintable	1 hour	2 hours	No	2-7 days	24 hours
Shrinkage	1%	30%	5%	5%	50%
Flexibility	40%	25%	25%	25%	25%
Cold Weather Extrusion	0°	20°	-35°	32°	-40°
VOC – compliant	Yes	Yes	Yes	Yes	Yes
Gap Filling	1"	1/2"	1/2"	1/2"	1/2"
Odor	Slight	Heavy	Mild	Mild	Moderate
Service Temperature (°F)	-75° to 350°	-20° to 200°	-45° to 350°	-40° to 180°	-40° to 180°

