

Safety Data Sheet
acc. to OSHA HCS



Printing date 03/17/2014

Reviewed on 03/17/2014

1 Identification

- **Product identifier**
- **Trade name:** TRIGGERFOAM PRO WINDOW & DOOR
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Polyurethane foam - low expansion (B2)
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Powers Fasteners, Inc.
2 Powers Lane
Brewster, NY 10509 / USA
- **Information department:**
Phone +1 800-524-3244
Fax +1 877-871-1965
- **Emergency telephone number:**
CHEMTREC: +1 703-741-5500 (24h Emergency Contact Information Only)
USA: 800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**
 - **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
Harmful
Harmful by inhalation. Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation.
.....
Irritant
Irritating to eyes, respiratory system and skin. May cause sensitisation by inhalation and skin contact.
.....
Extremely flammable
Extremely flammable.
.....
May cause long-term adverse effects in the aquatic environment. May cause harm to breastfed babies.
 - **Information concerning particular hazards for human and environment:**
The product has to be labeled due to the calculation procedure of international guidelines.
Warning! Pressurized container.
 - **Classification system:**
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.
 - **Label elements**
 - **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with directives on hazardous materials.
 - **Code letter and hazard designation of product:**
- 


Harmful
Extremely flammable
- **Hazard-determining components of labeling:**
diphenylmethanediisocyanate, isomeres and homologues
 - **Risk phrases:**
Extremely flammable.
Harmful by inhalation.
Irritating to eyes, respiratory system and skin.
Limited evidence of a carcinogenic effect.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2014

Reviewed on 03/17/2014

Trade name: TRIGGERFOAM WINDOW & DOOR

(Contd. of page 1)

May cause sensitisation by inhalation and skin contact.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 May cause long-term adverse effects in the aquatic environment.
 May cause harm to breastfed babies.

• **Safety phrases:**

Keep out of the reach of children.
 Keep away from sources of ignition - No smoking.
 Do not breathe spray.
 After contact with skin, wash immediately with plenty of soap and water.
 Wear suitable protective clothing and gloves.
 If swallowed, seek medical advice immediately and show this container or label.
 Use only in well-ventilated areas.

• **Special labeling of certain preparations:**

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
 Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
 This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.
 Contains isocyanates. See information supplied by the manufacturer.
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

• **Classification system:**

• **NFPA ratings (scale 0 - 4)**



Health = 2
 Fire = 0
 Reactivity = 3

• **HMIS-ratings (scale 0 - 4)**



Health = *2
 Fire = 0
 Reactivity = 3

• **Other hazards**

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

• **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

• **Dangerous components:**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	40-50%
115-10-6	dimethyl ether	1-10%
13674-84-5	tris(2-chlorisopropyl)-phosphate	1-10%
85535-85-9	alkanes, C14-17, chloro	1-10%
75-28-5	isobutane	1-10%
74-98-6	propane	<5%

USA

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2014

Reviewed on 03/17/2014

Trade name: TRIGGERFOAM WINDOW & DOOR

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Foam
CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Nitrogen oxides (NO_x)
Carbon monoxide (CO)
Hydrogen cyanide (HCN)
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Keep away from ignition sources
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2014

Reviewed on 03/17/2014

Trade name: TRIGGERFOAM WINDOW & DOOR

(Contd. of page 3)

See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure that suitable extractors are available on processing machines
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:**
Store away from oxidizing agents.
Do not store together with acids.
Do not store together with alkalis (caustic solutions).
- **Further information about storage conditions:**
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
Protect from humidity and water.
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:**
No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether	
WEEL	1000 ppm
75-28-5 isobutane	
REL	1900 mg/m ³ , 800 ppm
74-98-6 propane	
PEL	1800 mg/m ³ , 1000 ppm
REL	1800 mg/m ³ , 1000 ppm
TLV	Varies mg/m ³ , 1000 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2014

Reviewed on 03/17/2014

Trade name: TRIGGERFOAM WINDOW & DOOR

(Contd. of page 4)

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

- **Flash point:** -21 °C (-6 °F)

- **Ignition temperature:** 199 °C (390 °F)

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Heating may cause an explosion.

- **Explosion limits:**

Lower:	3.0 Vol %
Upper:	18.6 Vol %

- **Density:** Not determined.

- **Solubility in / Miscibility with**

Water:	Insoluble.
--------	------------

- **Solvent content:**

VOC content:	18.3 %
--------------	--------

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2014

Reviewed on 03/17/2014

Trade name: TRIGGERFOAM WINDOW & DOOR

(Contd. of page 5)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Hydrogen cyanide (prussic acid)
Carbon monoxide
Nitrogen oxides (NO_x)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3
-----------	--	---

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2014

Reviewed on 03/17/2014

Trade name: TRIGGERFOAM WINDOW & DOOR

(Contd. of page 6)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|---------------------|
| · UN-Number | |
| · DOT | UN1950 |
| · ADR, IMDG, IATA | 1950 |
| · UN proper shipping name | |
| · DOT, IATA | AEROSOLS, flammable |
| · ADR | 1950 AEROSOLS |
| · IMDG | AEROSOLS |
| · Transport hazard class(es) | |
| · DOT, IMDG, IATA | |
| · Class | 2.1 |
| · Label | 2.1 |
| · ADR | |
| · Class | 2 5F Gases |
| · Label | 2.1 |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | Void |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Gases |
| · EMS Number: | F-D,S-U |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Remarks: | LQ: 11 |

USA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2014

Reviewed on 03/17/2014

Trade name: TRIGGERFOAM WINDOW & DOOR

(Contd. of page 7)

15 Regulatory information

• **Safety, health and environmental regulations/legislation specific for the substance or mixture**

• **Sara**

• **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

• **Section 313 (Specific toxic chemical listings):**

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

• **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

• **Proposition 65**

• **Chemicals known to cause cancer:**

None of the ingredients is listed.

• **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

• **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

• **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

• **Carcinogenic categories**

• **EPA (Environmental Protection Agency)**

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

D;CBD

• **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

• **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

• **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

• **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

• **Hazard symbols:**



Harmful
Extremely flammable

• **Hazard-determining components of labeling:**

diphenylmethanediisocyanate, isomeres and homologues

• **Risk phrases:**

Extremely flammable.

Harmful by inhalation.

Irritating to eyes, respiratory system and skin.

Limited evidence of a carcinogenic effect.

May cause sensitisation by inhalation and skin contact.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

May cause long-term adverse effects in the aquatic environment.

May cause harm to breastfed babies.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/17/2014

Reviewed on 03/17/2014

Trade name: TRIGGERFOAM WINDOW & DOOR

(Contd. of page 8)

• Safety phrases:

Keep out of the reach of children.

Keep away from sources of ignition - No smoking.

Do not breathe spray.

After contact with skin, wash immediately with plenty of soap and water.

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

• Special labeling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

USA